



# HT502

## An easy-to-use 2 FXS port ATA

The HT502 is an analog telephone adapter (ATA) featuring 2 FXS ports that allows users to create a high-quality and manageable IP telephony solution. The product's inclusion of an integrated NAT router and dual 10/100Mbps Ethernet WAN and LAN ports enables a shared broadband connection between multiple Ethernet devices as well as the extension of VoIP services to analog phones.



Supports 2 SIP profiles through 2 FXS ports and single 10/100Mbps port



TLS and SRTP security encryption technology to protect calls and accounts



Automated provisioning options include TR-069 and XML config files



**3 WAY**  
Supports 3-way voice conferencing



Failover SIP server automatically switches to secondary server if main server loses connection



Supports T.38 Fax for creating Fax-over-IP



Supports a wide range of caller ID formats



Use with Grandstream's UCM series of IP PBXs for Zero Configuration provisioning



Supports advanced telephony features, including call transfer, call forward, call-waiting, do not disturb, message waiting indication, multi-language prompts, flexible dial plan and more

## Interfaces

**Telephone Interfaces** Two (2) FXS port (RJ11)

**Network Interfaces** Two (2) 10/100Mbps ports (RJ45)

**LED Indicators** Power,WAN, LAN, PHONE 1 and PHONE 2

**Factory Reset Button** Yes

## Voice, Fax, Modem

**Telephony Features** Caller ID display or block, call waiting, flash, blind or attended transfer, forward, hold, do not disturb, 3-way conference

**Voice Codexs** G.711 with Annex I (PLC) and Annex II (VAD/CNG), G.723.1, G.729A/B/E, G.728, G.726-40/32/24/16, iLBC

**Fax Over IP** T.38 compliant Group 3 fax relay up to 14.4kbps, Fax datapump V.17, V.19, V.27ter, V.29 for T.38 fax relay

**Short/Long Haul Ring Load** REN 3: Up to 150 ft on 24 AWG lines

**Caller ID** Bellcore type 1 & 2, ETSI, BT, NTT and DTMF-based CID

**Disconnect Methods** Polarity Reversal/Wink

## Signaling

**Network Protocols** TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS, DHCP, NTP, TFTP, TELNET, PPPoE, STUN

**QoS** Layer 2 (802.1Q VLAN/802.1p) and Layer 3 (ToS, Diffserv, MPLS)

**DTMF Method** RFC2833 and/or SIP INFO

**Provisioning and Control** UPnP, HTTP, HTTPS, TELNET, TFTP, TR069, secure and automated provisioning using AES encryption, syslog

## Security

**Media** SRTP

**Control** TLS/SIPS/HTTPS

**Management** Syslog support, telnet, remote management using web browser

## Physical

**Universal Power Supply** Input: 100-240VAC, 50-60Hz  
Output: 12V VDC, 0.5A

**Environmental** Operational: 32° ~ 104°F or 0° ~ 40°C;  
Storage: -10 ~ 130°F  
Humidity: 10 - 90% non condensing

**Dimensions** 25mm x 115mm x 75mm (when laying flat)

**Compliance** FCC (Part 68 & 15B), C-Tick, AS/NZS CISPR22, CISPR24, CE, EN55022, EN55024, TBR21, EN60950, EN61000-3-2, EN61000-3-3, UL (Power supply)