



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

**Certification ID: WFA136323** 

# **Product Info**

**Date of Certification** June 19, 2025

**Company** Grandstream Networks, Inc.

Product Name Tri-band Wi-Fi 7 Access Point

Product Model Variant GWN7672

Model Number GWN7672

**Category** Routers

**Sub-category** Enterprise/Service Provider Access Point, Switch/Controller or Router

# **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Passpoint® Release 3

Network management WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Enterprise 2022-12 WPA3<sup>™</sup>-Personal 2024-10

WPA™-Enterprise WPA™-Personal

Wi-Fi Enhanced Open™ 2023-12

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities

Spectrum & Regulatory
Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ ac
Wi-Fi CERTIFIED™ b



**Certification ID: WFA136323** 



Summary of Certifications (continued)		Page 2 of 5
CLASSIFICATION	CERTIFICATION	
Wi-Fi (MAC/PHY)	Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n	



**Certification ID: WFA136323** 



Role: Access Point	Page 3 of 5			
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture	RF Architecture		
linux 5.4.213	Bands Supported	Transmit (Tx)	Receive (Rx)	
Wi-Fi Component Firmware 0.10.31.2(init)	2.4 GHz	2	2	
0.10.31.2(IIIII)	5 GHz	2	2	
	6 GHz	2	2	
Operatificant in the				
Certifications				
2.4 GHz Spectrum Capabilities	Passpoint® Relea	Passpoint® Release 3 (continued)		
20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz	Terms and Conditions  Venue Information			
40 WHZ GHAIRICI WIGHT III Z.4 GHZ	venue information			
5 GHz Spectrum Capabilities	Protected Management Frames			
20 MHz Channel Width in 5 GHz	Spectrum & Regulatory			
40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz	802.11d			
160 MHz Channel Width in 5 GHz	802.11h			
6 GHz Spectrum Capabilities	WMM®			
20 MHz Channel Width in 6 GHz	WPA2™-Enterprise 2018-04			
40 MHz Channel Width in 6 GHz		·		
80 MHz Channel Width in 6 GHz 160 MHz Channel Width in 6 GHz	EAP methods			
320 MHz channel width in 6 GHz	WPA2™-Personal	2021-01		
Passpoint® Release 3 WPA3™-Enterprise 2022-12				
Roaming Consortium Selection		EAP methods		
Tourning Consortium Colociton	LAI IIIEIIIUUS			



**Certification ID: WFA136323** 



Role: Access Point Page 4 of 5

## WPA3™-Enterprise 2022-12 (continued)

192-bit security

#### WPA3™-Personal 2024-10

AKM 24

**Beacon Protection** 

#### **WPA™-Enterprise**

#### WPA™-Personal

#### Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list Cellular Data aware

#### Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

**BSRP** Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

#### Wi-Fi CERTIFIED 6® (continued)

MU-RTS Trigger frame

M-BSSID

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

**UL OFDMA** 

Wi-Fi 6E

## Wi-Fi CERTIFIED 7™

Advertised TID-to-link mapping

A-MPDU with A-MSDU

**BSRP** Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)

DL MU-MIMO

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

EPCS (Emergency Preparedness Communications Services)

priority access

LDPC Rx

LDPC Tx

Load Balancing in MLO

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Rx



**Certification ID: WFA136323** 



Role: Access Point Page 5 of 5

## Wi-Fi CERTIFIED 7™ (continued)

MCS 12-13 Tx

Multi-link reconfiguration - AP removal

Multi-RU

MU-RTS Trigger frame

Operating mode indication

Operating mode indication for 320 MHz

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMO

Triggered uplink access optimization

**UL OFDMA** 

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

Extended 5 GHz Channel Support

LDPC Rx

LDPC Tx

MCS 8-9 Rx

**Short Guard Interval** 

STBC

SU beamformer

## Wi-Fi CERTIFIED™ b

# Wi-Fi CERTIFIED™ g

## Wi-Fi CERTIFIED™ n

A-MPDU Tx

**OBSS** on Extension Channel

# Wi-Fi CERTIFIED™ n (continued)

Short Guard Interval

STBC

Wi-Fi Enhanced Open™ 2023-12