



Partner Marketing Kit



GSC3570

Messaging Strategy

GSC3570

Tagline	HD Intercom and Facility Control Station
Subhead	<i>The GSC3570 provides users with streamlined control of facility communications, intercoms, door access and physical security devices.</i>
Positioning	The GSC3570 is a powerful intercom and facility control station designed to provide businesses with a dedicated device to manage facility communications, door access, physical security and more. This device can be wall-mounted or placed on a desktop as a solution for easy door control, intercom and paging communication, security camera management and facility-wide UC integration. This SIP intercom and facility control station is designed to seamlessly integrate with Grandstream's entire range of products, including the GDS series of Door Access devices, GSC series intercom and paging devices, security cameras and more. The GSC3570 is ideal for any deployment scenario where facility access, communications and security need to be centrally monitored and controlled.
Key Differentiators	<ul style="list-style-type: none">• Centralized control of all Grandstream solutions, including intercom, door access, and physical security products• Dual-band 802.11 ac Wi-Fi• 7 inch 1024x600 capacitive touch screen• 4x alarm input ports and 1x alarm output port for customized deployments• Secure Boot & Data, TLS and SRTP security encryption technology to protect calls and accounts• Full duplex 2-way HD audio with advanced echo cancellation• Supports PoE to provide a network connection to the device• Can be wall-mounted or placed on a desktop

[French](#)

[Italian](#)

[Polish](#)

[Spanish](#)

[German](#)

[Portuguese](#)

[Russian](#)

GSC3570 Datasheet



HD Intercom and Facility Control Station GSC3570

The GSC3570 is a powerful intercom and facility control station designed to provide businesses with a dedicated device to manage facility communications, door access, physical security and more. This device can be wall-mounted or placed on a desktop as a solution for easy door control, intercom and paging communication, security camera management and facility-wide UC integration. The GSC3570 features a 7-inch touch screen LCD and full duplex 2-way HD audio. It offers a flexible network connectivity through 100Mbps network port with PoE or integrated dual-band Wi-Fi support. This SIP intercom and facility control station is designed to seamlessly integrate with Grandstream's entire range of products, including the GDS series of Door Access devices, GSC series intercom and paging devices, security cameras and more. The GSC3570 is ideal for any deployment scenario where facility access, communications and security need to be centrally monitored and controlled.



7 inch 1024x600 capacitive touch screen



Dual-band 802.11 ac Wi-Fi



4x alarm input ports and 1x alarm output port for customized deployments



Full duplex 2-way HD audio with advanced echo cancellation



Secure Boot & Data, TLS and SRTP security encryption technology to protect calls and accounts



Supports PoE to provide a network connection to the device

Protocol/Standards	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LDAP, 802.1x, TLS, SRTP, IPv6
Network Interface	Dual switched 10/100Mbps ports
Graphic Display	7" 1024x600 capacitive touch screen TFT LCD with Home key
Wi-Fi	Yes, dual-band 802.11 a/b/g/n/ac (2.4GHz & 5GHz)
Alarm Input	4 Channels, including 1 Optocoupler, Vin < 15V (IN+) and 3 Dry Contact (IN1-3), for low voltage devices such as a door sensor, other switch contact, button etc.
Alarm Output	1 Channel/Relay, 125VAC/0.5A or 30VDC/2A, Normal Open or Normal Close, for high voltage devices such as, an electric lock or light switch
LED Indicator	Yes, Dual color LED for event indication
Micro SD/TF Supported	Yes, up to 256G
Voice Codescs and Capabilities	G.711u/a, G.722 (wide-band), G.726-32, ILBC, Opus, G.729A/B, DTMF (In audio, RFC2833, SIP INFO), VAD, CNR, AEC, PLC, ABR, AGC, ANS
Video Decoders and Capabilities	H.264 BP/MP/HP, video resolution up to 720p, frame rate up to 30 fps, bit rate up to 2Mbps
Telephony Features	4 SIP Accounts, Hold, Call Waiting, Call Log, Auto Answer, etc.
Sample Applications	Local apps: Contacts, Call History, Settings, Voicemail, Clock API/SDK available to allow integration with 3rd party door system products
Operating System	Linux
HD Audio	Yes, Dual speakers with support for wideband audio and media play in stereo, acoustic echo cancellation
QoS	Layer 2 (802.1Q, 802.1p), 802.11e and Layer 3 (ToS, DiffServ, MPLS) QoS
Security	Secure Boot & Data, Double images for high reliability, random administrator password, user and administrator level passwords, MD5 and MD5-session based authentication, 256-bit AES based secure configuration file, SRTP, TLS, 802.1x media access control
Multi-language	English, Chinese, Dutch, Spanish, French, Italy, Portuguese, and Russian
Upgrade/Provisioning	Firmware upgrade via TFTP/HTTP/HTTPS, mass provisioning using AES encrypted XML configuration file, manual upload
Power & Green Energy Efficiency	2-pin DC input: 12VDC/1A Integrated PoE: IEEE 802.3af Class 3, power consumption <10W Micro USB input: 5VDC/2A
Temperature and Humidity	Operation: -10°C to 50°C, Storage: -20°C to 60°C, Humidity: 10% to 90% Non-condensing
Physical	Unit Dimension: 224.5 x 149.5 x 36.5mm; Unit Weight: 517g Entire Package Dimension: 265 x 180 x 54mm; Entire Package Weight: 880g
Package Contents	GSC3570, quick installation guide, wall mount bracket, and desktop stand (optional)
Compliance	FCC, CE, RCM, IC
Optional Accessories	GDS3710 & GDS3705

Translations

[English](#)

[French](#)

[German](#)

[Italian](#)

[Polish](#)

[Portuguese](#)

[Russian](#)

[Spanish](#)

www.grandstream.com

www.grandstream.com

3.2020.05

GSC3570 Sales Kit

The sales kit is a guide to everything you need to know about selling the GSC3570, HD Intercom and Facility Control Station.

The Sales Kit includes:

- Overview and Basics
- Key Differentiators
- Comparison vs. Competition
- Deployment Scenarios
- Integration with other Grandstream Products

Translations

[English](#)

[Portuguese](#)

[Spanish](#)

GSC3570 - Sales Kit Overview and Basics

About the GSC3570

The GSC3570 is a powerful intercom and facility control station designed to provide businesses with a dedicated device to manage facility communications, door access, physical security and more. This device can be wall-mounted or placed on a desktop as a solution for easy door control, intercom and paging communication, security camera management and facility-wide UC integration. The GSC3570 features a 7-inch touch screen LCD and full duplex 2-way HD audio.

Product Positioning

This SIP intercom device is designed to seamlessly integrate with Grandstream's entire range of products, including our SIP door systems, security cameras, and intercom and paging devices. The GSC3570 is ideal for any deployment scenario where facility access, communications and security need to be centrally monitored and controlled.



Full-band and wide-band audio codec



7" 1024x600 capacitive touch



Integrated Wi-Fi



Full-duplex 2-way HD audio with advanced echo cancellation

Competitive Features

- 7 inch 1024x600 capacitive touch screen
- Integrated dual-band 802.11 a/b/g/n/ac Wi-Fi
- 4x alarm input ports and 1x alarm output port for customized deployments
- Full duplex 2-way HD audio with advanced echo cancellation
- Supports PoE to provide a network connection to the device
- 4 SIP accounts/lines
- Can be wall-mounted or placed on a desktop

GSC3570 Key Technical Specifications

Network Interfaces	Dual switched 10/100Mbps ports
Graphic Display	7" 1024x600 capacitive touch screen TFT LCD with Home Key
Wi-Fi	Yes, dual-band 802.11a/b/g/n/ac (2.4GHz & 5GHz)
HD Audio	Yes, Dual speakers with support for wideband audio and media play in stereo, acoustic echo cancellation
Telephony Features	4 SIP accounts, hold, call waiting, call log, auto answer, etc
Auxiliary Ports	4 x Alarm Input, 1 x Alarm Output, Micro SD card slot
Security	Secure Boot & Data, Double images for high reliability, random administrator password, user and administrator level passwords, MD5 and MD5-session based authentication, 256-bit AES based secure configuration file, SRTP, TLS, 802.1x media access control

GSC3570 PowerPoint Presentation



Translations

[English \(PowerPoint\)](#)

[English \(PDF\)](#)

[Portuguese \(PowerPoint\)](#)

[Portuguese \(PDF\)](#)

[Spanish \(PowerPoint\)](#)

[Spanish \(PDF\)](#)

GSC3570 Marketing Materials

Email

[GSC3570 Email Editable File \(InDesign\)](#)

[GSC3570 Email \(PDF\)](#)

[GSC3570 Email Text \(Word\)](#)

[GSC3570 Verticals Image \(PNG\)](#)


[GSC3570 Email Banner \(PSD\)](#)

[GSC3570 Email Banner \(PNG\)](#)

Email Signature


[GSC3570 Email Signature Editable File \(PSD\)](#)

[GSC3570 Email Signature English \(PNG\)](#)



Press Release

[Grandstream Releases a New HD Intercom and Facility Access Control Station \(Word\)](#)







New Product Launch!

Grandstream's New HD Intercom and Facility Access Control Station


The GSC3570 is a powerful intercom and facility control station designed to provide businesses with a dedicated device to manage facility communications, door access, physical security and more. This device can be wall-mounted or placed on a desktop as a solution for easy door control, intercom and paging communication, security camera management and facility-wide UC integration. This SIP intercom and facility control station is designed to seamlessly integrate with Grandstream's entire range of products, including the GDS series of Door Access devices, GSC series intercom and paging devices, security cameras and more.

Key Technical Specifications

- Centralized control of all Grandstream solutions, including intercom, door access, and physical security products
- Dual-band 802.11 ac Wi-Fi
- 7 inch 1024x600 capacitive touch screen
- 4x alarm input ports and 1x alarm output port for customized deployments
- Secure Boot & Data, TLS and SRTP security encryption technology to protect calls and accounts
- Full duplex 2-way HD audio with advanced echo cancellation
- Supports PoE to provide a network connection to the device
- Can be wall-mounted or placed on a desktop



Deployment Scenarios



A grid of eight images showing various deployment scenarios for the GSC3570. The scenarios are: Apartment Buildings/Modern Residences, Hotel Conference & Banquet Rooms, Healthcare/Retirement Facilities, Modern Offices, Security Departments, and Warehouses.

Contact Us to Learn More

List how your customers can contact you to learn more about this product

GSC3570 Digital Marketing - Social Template

Create your own Social Media Image

Use the editable template to customize your own social image, or create your own using the elements provided below. We recommend using the text provided in the messaging and strategy on pg.2.

Social Image w/ text Template:

[Editable Photoshop File](#)

[Social Image w/ text_English \(PNG\)](#)

Stock Photos (2 Options)

[Option 1](#)

[Option 2](#)

[Option 3](#)

Icons (white):

[All 4 Icons](#)

[Wi-Fi](#)

[Security](#)

[Alerts](#)

[Touch Screen](#)

Product Images

[GSC3570](#)

Logo (add your own or use Grandstream's)

[Logo_white](#)

[Logo_blue](#)

Official Grandstream Colors:

Deep Blue:



RGB: 42 / 83 / 137
#295288

Aqua Blue:



RGB: 70 / 168 / 202
#46A7C9

Grey:



RGB: 156 / 158 / 159
#9C9D9F

Orange (Secondary Color):



RGB: 255 / 83 / 13
#FF530D



Tagline
(from Messaging and Strategy on Pg.2)

GSC3570_front

Icons

Subhead
(from Messaging and Strategy on Pg.2)

GSC3570 Digital Marketing - Social Paid / Cover Photo

Paid Social Ad (no text)


[GSC3570 Social Image No Text](#)

[GSC3570 Social Image w/ icons](#)

[GSC3570 Social Lifestyle Image](#)

Paid/Non-Paid Social Copy

[GSC3570 Suggested Social Copy](#)



Cover Photo

[Facebook Cover Photo Editable \(PSD\)](#)

[Facebook Cover Photo English \(PNG\)](#)



GSC3570 Digital Advertising - Banner Ads Template

What are Banner Ads?

Banner advertising is synonymous with display ads. They're placed in high-traffic locations on webpages, creating brand awareness and generating click-throughs, purchases, and leads. These high-visibility locations include the front, bottom, or the side of a webpage; places where the eyes of browsers usually wander.

See the next page for recommended sizing

Ad Banner 300x250

[Editable Photoshop File \(300x250 Sample\)](#)

[Ad Banner Sample 300x250 English \(PNG\)](#)

Product Images

[GSC3570_front](#)

Logo (add your own or use Grandstream's):

[Logo_white](#)

[Logo_blue](#)

Official Grandstream Colors:

Deep Blue:

RGB: 42 / 83 / 137
#295288

Aqua Blue:

RGB: 70 / 168 / 202
#46A7C9

Grey:

RGB: 156 / 158 / 159
#9C9D9F

Orange (Secondary Color):

RGB: 255 / 83 / 13
#FF530D



The banner ad is set against a dark blue background. At the top, the headline "HD Intercom and Facility Control Station" is in white. Below it, a subhead in white text states: "The GSC3570 provides users with streamlined control of facility communications, intercoms, door access and physical security devices." In the center is a white tablet displaying the Grandstream interface. At the bottom is an orange rounded rectangle with the text "Learn More".


Tagline
(from Messaging and Strategy on Pg.2)

CTA (Call to Action)
Tells the site users to do something such as sending them to a product page


Subhead
(from Messaging and Strategy on Pg.2)

GSC3570 Digital Advertising - Banner Ads Sizing

Mobile: Common Ad Dimensions



Computer: Common Ad Dimensions



Marketing Assets

1. Product Images

- [front](#)
- [side](#)
- [wall mounted](#)
- [desktop placement](#)



Front



Side



Wall Mounted



Desktop Placement

2. Datasheet Feature icons

- [Wi-Fi](#)
- [Alerts](#)
- [Touch Screen](#)
- [HD Audio](#)
- [Security](#)
- [PoE](#)



Wi-Fi



Alerts



Touch Screen



HD Audio